

MAHINDRA

T R A C T O R S

2810 HST



Cultivate
Your
Dreams™

MAHINDRA 2810 HST



3-YEAR
WARRANTY*

SUPERIOR PERFORMANCE:

- **Higher lift capacity:** Handle larger implements...Get work done a lot faster
- **Heavy-duty components:** Tough and rugged...Keep right on performing day after day
- **Sturdier chassis:** Greater stability...Keeps you safe while handling rigorous work
- **Heavier chassis:** Additional weight...Provides extra traction

2810 HST SPECIFICATIONS

ENGINE - 3A139A-DY1

Type: Four stroke, indirect injection, water-cooled, diesel
Cylinders: 3
Engine HP (kW) @ RPM: 28 (20.9) @ 2700
Compression Ratio: 22:1
Displacement: Cubic inch (cc): 85 (1393)

ELECTRICAL

Battery Capacity: 12 volt, 60 amp hours
Alternator: 12 volt, 50 amps

TRANSMISSION

Type: HST - 3 Ranges
No. of Speeds: Infinite

FRONT WHEEL DRIVE

Type: Mechanical

STEERING

Type: Hydrostatic power
Pump Output (gallons/minute): 4.55

BRAKES

Type: Wet disc

HYDRAULIC SYSTEM

Type: Open Center, full-live hydraulic with position control
Pump Output (gallons/minute): 6.3
3-Point Linkage: Category 1, with check chains
Lift Capacity (lbs.): 2080

PTO

Type: Independent PTO with safety mechanism and electro-hydraulic clutch
Rear PTO RPM: 540 @ 2775 engine rpm
PTO HP (kW): 22.5 (16.8)

OPERATING WEIGHT

Total (lbs.): 3064

DIMENSIONS

Overall Length Inches (mm): 114 (2896)
Overall Width Inches (mm): 52 (1321)
Turning Radius Minimum (mts): 2.5

Industrial
Front: 43 x 16-20
Rear: 10 x 16.5

Turf
Front: 41 x 14-20
Rear: 28 x 8.5-15



Cultivate
Your
Dreams™