

MAHINDRA

T R A C T O R S

5500 4WD



Cultivate
Your
DreamsSM

MAHINDRA 5500 4WD



3-YEAR
WARRANTY*

SUPERIOR PERFORMANCE:

- **Higher lift capacity:** Handle larger implements...Get work done a lot faster
- **Heavy-duty components:** Tough and rugged...Keep right on performing day after day
- **Sturdier chassis:** Greater stability...Keeps you safe while handling rigorous work
- **Heavier chassis:** Additional weight...Provides extra traction

5500 4WD SPECIFICATIONS

ENGINE – NE452

Type: Four stroke, direct injection, water-cooled, diesel

Cylinders: 4

Maximum Engine HP (kW) @ RPM: 54 (40.3) @ 2100

Compression Ratio: 19.4:1

Displacement: Cubic inch (cc): 186 (3055)

Cylinder Sleeve: Wet replaceable

ELECTRICAL

Battery Capacity: 12 volt, 96 amp hours

Alternator: 12 volt, 36 amp

CLUTCH

Type: Dual

TRANSMISSION

Type: Forward-Reverse Synchro-Shuttle with full synchromesh

Number of Gears: 8 forward, 8 reverse

STEERING

Type: Hydrostatic power

BRAKES

Type: Wet disc

HYDRAULIC SYSTEM

Type: Open Center, full-live hydraulic with position and draft control

Pump Output (gallons/minute): 11

3-Point Linkage: Category 1 and 2 with telescopic check chains

Lift Capacity (lbs.): 3968

Auxiliary Remote Valves: 1 standard

PTO

Type: Independent

PTO RPM: 540 & 1000 @ 2100 engine rpm

Maximum PTO HP (kW): 44 (32.8)

OPERATING WEIGHT

Total (lbs.): 6230

DIMENSIONS

Overall Length Inches (mm): 150 (3810)

Overall Width Inches (mm):** 77 (1956)

Turning Radius Minimum Feet (mts): 11.5 (3.5)

Ag
Front: 9.5 x 24
Rear: 14.9 x 28

Industrial
Front: 12.5/80 x 18
Rear: 16.9 x 24



Cultivate
Your
Dreams™

Specifications and design subject to change without notice. ©2002 Mahindra USA. MAH-031802
* 3-year engine and power train warranty – see dealer for details.
** Tread adjustment 4 step